

Hillside Slide Model: Chervin

Specifications

Description: Open fiberglass flume designed for hillside and landscape applications.

Slide Run: 92'

Features

- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- · Stairs & Platform: available.
- 600-800 gpm water flow required.
- Splash down dimension 13' x 20'
- Minimum water depth: 3'
- USA Made

tructures PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231 www.naturalstructures.com - info@naturalstructures.com

Slide Entrance Height: 10' 3"

Platform Size: N/A

Space Requirements: 20' 4" x 45' 3"

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- · Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric;
 (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.

*Space requirements may vary with options chosen.