



# Hillside Slide Model: Timber-lee

## Specifications

**Description:** Double combo flume slide featuring (1) polyethylene tunnel flume and (1) fiberglass open flume.

**Slide Run:** (Fiberglass) 297' (Poly) 150'  
**Elevation Height:** 34' above water level

**Platform Size:** N/A

**Space Requirements:** 132' 11" x 44'

## Features

- 30" inside diameter polyethylene flume.
- 36" inside diameter fiberglass flume.
- Polyethylene Flume: color impregnated UV stabilized.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Stairs & Platform: available.
- Polyethylene: 50-150 gpm water flow required.
- Fiberglass: 600-800 gpm water flow required.
- Splash down dimension 23' x 20'
- Minimum water depth: 3'
- USA Made

## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
 www.naturalstructures.com - info@naturalstructures.com

\*Space requirements may vary with options chosen.