



## Hillside Slide Model: Hathaway

### Specifications

**Description:** Single polyethylene flume designed for hillside and landscape applications.  
**Centerline Run:** 38' 6"

**Slide Entrance Height:** 9' 9"  
**Space Requirement:** 36' 1" x 16' 0"

### Features

- 30" inside diameter polyethylene flume.
- Polyethylene Flume: color impregnated UV stabilized.
- Stairs & Deck: available.
- Multiple stair locations & configurations.
- Stairs & Platform: determined by the slope.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 250 gpm required.
- Splash down dimension 13' 0" x 20' 0"
- Minimum water depth: 3' 6"
- USA Made

### Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
www.naturalstructures.com - info@naturalstructures.com