



Fiberglass Water Slide Model 2100*

Specifications

Description: Single fiberglass open flume water slide.

Centerline Run: 23' 3"

Entry Height: 5' 3" *

Platform Size: 6' 10" x 10' 6"

Space Requirements: 14' 7" x 26' 7"

Features

- 8' wide (96") open fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 300-500 gpm water flow required.
- Splash down dimension: 18' 0" x 14' 0"
- Minimum water depth: 3' 0" (within 6" of water level) or 1' 6" with landing pad
- USA Made

Series Models Available*

Model	Slide Entrance Height	Centerline Run
2100	5' 3"	23' 3"
2101	6' 5"	26' 8"
2102	8' 2"	31' 9"
2103	9' 11"	36' 11"

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*See other models for more entry height options