



Combination Water Slide Model 1914

Specifications

Description: Combination flume water slide featuring: (1) polyethylene flume with (3) 270° curves & (2) 32" I.D. closed & 36" I.D. open fiberglass flume.

Centerline Run: (1): 148' 11" (2): 60' 3"
Entry Height: (1): 24' 5" (2): 23' 11"
Platform Size: 8' x 8'
Space Requirements: 35' 5" x 44' 0"

Features

- 32" inside diameter closed flume fiberglass.
- 36" inside diameter fiberglass flume.
- 30" inside diameter polyethylene flume.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Polyethylene Flume: color impregnated UV stabilized.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Water flow required: Fiberglass: 150-200 gpm; Polyethylene: 30-60 gpm.
- Splash down dimension: 33' 0" x 30' 0"
- Minimum water depth: 3' 0"
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814

(541) 523-0224 (800) 252-8475 Fax (541) 523-0231

www.naturalstructures.com - info@naturalstructures.com