



Drop Slide Pool Slide Model 5022

Specifications

Description: 30" I.D. double flume drop slide

Centerline Runs: 20' 0" & 18' 10"

Space Requirements: 21' 2" x 28' 5" *

Entry Height: 10' 6"

Exit Height (drop): 3' 0" & 2' 0"

Platform Size: 4' x 4'

Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: 8" rise, 8" tread, 24" wide; Aqua-Plast coated textured aluminum surface.
- Multiple stair locations & configurations.
- Optional Fabric Roof (*shown*)
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow recommended;
8 to 40 gpm required.
- Splash down dimension 12' 6" x 20' 0"
- Minimum water depth: 9' 0"
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (*if applicable*).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.