



Triple Flume Drop Slide Model 5023

Specifications

Description: 30" I.D. closed polyethylene triple flume drop slide

Centerline Runs: 16' 11", 12' 7" & 19' 3"

Entry Height: 8' 8"

Exit Height (drop): 5' 0", 3' 1-³/₁₆", 2' 0-³/₄"

Platform Size: 4' x 8'

Space Requirements: 23' 8" x 18' 9" *

Features

- 30" inside diameter polyethylene flumes.
- Flume: color impregnated UV stabilized.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow recommended
- Splash down dimension 28' 6" x 20' 0"
- Minimum water depth: Flume 1: 12' 0"; Flumes 2 & 3: 9' 0"
- USA Made

Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat, except stair treads and deck which are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs; (d) 8" rise, 8" tread, 24" wide.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.