



Triple Flume Water Slide Model 1666

Specifications

Description: Triple flume 30" I.D. polyethylene slide featuring Cloverleaf, Switchback and figure 8 curves.

Centerline Run: 144' 3", 130' 11", & 160' 0"

Entry Height: 23' 11"

Platform Size: 12' x 16'

Space Requirements: 58' 7" x 46' 10" *

Features

- 30" inside diameter polyethylene flume
- Flume: color impregnated UV stabilized
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 48" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts
- Designed with flexibility to allow for sloping pool decks
- Deck top mounted
- 50 gpm water flow required (each flume)
- Splash down dimension: 22' 5" x 20' 0"
- Minimum water depth: 3' 6"
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 36" width; (b) Inner handrails (if applicable); (c) Spiral stairs
- Stair Configurations: Many variations available
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.