



Fiberglass Water Slide Model 1884

Specifications

Description: Triple fiberglass and polyethylene flume combination slide.
Slide Run: Fiberglass (open) 217' 0"; Polyethylene (closed) (1) 167' 0"; (2) 142' 0"

Platform Height: 23' 11"
Platform Size: 8' x 12'
Space Requirements: 41' 3" x 57' 7"

Features

- 36" inside diameter fiberglass open flume.
- 30" inside diameter polyethylene closed flume.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Polyethylene Flume: color impregnated UV stabilized.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 48" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Water flow required: Open: 800 gpm; Closed: 30 to 60 gpm.
- Splash down dimension 42' 0" x 20' 0"
- Minimum water depth: 3' 0"
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 36" width; (b) Inner handrails (if applicable); (c) Spiral stairs
- Stair Configurations: Many variations available
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.

Natural Structures
 PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.