



Fiberglass Water Slide Model 1820

Specifications

Description: Single open flume fiberglass slide featuring (2) 360° reverse curves.

Centerline Run: 78' 10"

Entry Height: 11' 1"

Platform Size: 6' x 8'

Space Requirements: 32' 7" x 23' 1"

Features

- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 600-800 gpm water flow required.
- Splash down dimension: 13' x 20'
- Minimum water depth: 3'
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231
www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.