



Hillside Slide Model 1683

Specifications

Description: Double flume polyethylene body slides

Centerline Run: 178' 3" & 146' 7"

Entry Height: 30' 2" above waterline

Platform Size: *Tower and stairs done by others.

Space Requirements: 94' 8" x 41' 0"

Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Stairs & Platform: available.
- Stainless steel base plates, hardware and anchor bolts.
- Flume posts are required in accordance to the elevation.
- 50 gpm water flow (each flume) recommended; 30 to 60 gpm required
- Splash down dimension 12' 6" x 20' 0"
- Minimum water depth: 5'
- USA Made.

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814

(541) 523-0224 (800) 252-8475 Fax (541) 523-0231

www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.