



Hillside Slide Model: Holman

Specifications

Description: Single polyethylene flume designed for hillside and landscape applications.
Slide Run: 33'

Elevation Height: 7' 6"
Slide Entrance Height: 7' 6"
Space Requirements: 18' 2" x 12'

Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Stairs & Platform: available.
- Flume posts are required in accordance to the elevation
- 14-20 gpm water flow required.
- Splash down dimension 12' 6" x 20'
- Minimum water depth: 5'
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.