



## Hillside Slide Model: Tyler Hill

### Specifications

**Description:** 36" I.D. Fiberglass flume slide featuring (2) 360° curves.  
**Centerline Run:** 194' 5"

**Entry Height:** 25' 8"

**Platform Size:** N/A \*Tower and stairs done by others.

**Space Requirements:** 41' 0" x 74' 7" \*

### Features

- 36" inside diameter fiberglass flume.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Stairs & Platform: available.
- Water flow required: 600-800 gpm.
- Splash down dimension: 13' 0" x 20' 0"
- Minimum water depth: 9' 0"
- USA Made

### Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.