



Landscape Water Slide Model Kaufman 1

Specifications

Description: Single closed & open fiberglass flume slide featuring (3) 360° curves.

Centerline Run: 173' 8"

Entry Height: 22' 9"

Platform Size: Platform and stairs by others.

Space Requirements: 28' 2" x 38' 2"

Features

- 32" inside diameter closed fiberglass flume.
- 36" inside diameter open fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Stairs & Platform: available.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 800-1200 gpm water flow required.
- Splash down dimension: 13' 0" x 20' 0"
- Minimum water depth: 3' 0"
- USA Made



Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814

(541) 523-0224 (800) 252-8475 Fax (541) 523-0231

www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.