



Drop Slide Model 5008

Specifications

Description: 30" I.D. single flume drop slide.
Centerline Run: 13' 1"
Deck Space Requirement: 14' 11" x 13' 9" *

Entry Height: 10' 6"
Exit Height (drop): 4' 11^{-5/16}"
Platform Size: 4' x 4'

Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: 8" rise, 8" tread, 24" wide; Aqua-Plast coated textured aluminum surface.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 14-20 gpm water flow recommended; 8 to 40 gpm required.
- Splash down dimension 12' 6" x 20' 0"
- Minimum water depth: 12' 0"
- USA Made

Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat, except stair treads and deck which are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.