



# Fiberglass Water Slide Model 2100\*

## Specifications

**Description:** Single fiberglass open flume water slide.

**Centerline Run:** 23' 3"

**Entry Height:** 5' 3" \*

**Platform Size:** 6' 10" x 10' 6"

**Space Requirements:** 14' 7" x 26' 7"

## Features

- 8' wide (96") open fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 300-500 gpm water flow required.
- Splash down dimension: 18' 0" x 14' 0"
- Minimum water depth: 3' 0" (within 6" of water level) or 1' 6" with landing pad
- USA Made

Series Models Available\*

Model	Slide Entrance Height	Centerline Run
2100	5' 3"	23' 3"
2101	6' 5"	26' 8"
2102	8' 2"	31' 9"
2103	9' 11"	36' 11"



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 [www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.

\*See other models for more entry height options