



## Double Flume Water Slide Model 1678

### Specifications

**Description:** Double flume 30" I.D. polyethylene slide, one 360° and one 180° turn.  
**Centerline Run:** 48' 6" & 29' 5"

**Entry Height:** 11' 0"

**Platform Size:** 8' x 8'

**Space Requirements:** 25' 5" x 20' 11" \*

### Features

- 30" inside diameter polyethylene flume
- Flume: color impregnated UV stabilized
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts
- Designed with flexibility to allow for sloping pool decks
- 20 gpm water flow (each flume) recommended; 20 to 40 gpm required.
- Splash down dimension 12' 6" x 20' 0"
- Minimum water depth: 3' 0"
- USA Made

### Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs
- Stair Configurations: Many variations available
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
 www.naturalstructures.com - info@naturalstructures.com

\*Space requirements may vary with options chosen.