

Triple Flume Water Slide Model 2047

Specifications

Description: Triple fiberglass flume water slide

with fiberglass exit lanes

Centerline Run: Green Flume 137' 5"; Blue Flume 158' 11"; Red Flume 80' 7"

Features

- 36" inside diameter open fiberglass flume.
- 32" inside diameter closed fiberglass flume.
- Fiberglass Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Flume posts are required in accordance to the elevation.
- Fiberglass exit lanes.
- Self-enclosed recirculating system (no pool required)
- Water flow required: *Green Flume* 500-700 gpm; *Blue Flume* 600-800 gpm; *Red Flume* 150-200 gpm.
- USA Made

PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231 www.naturalstructures.com - info@naturalstructures.com

Entry Height: Green Flume 18' 10"; Blue Flume 22' 11"; Red Flume 29' 4"

Platform Size: 7' 9" x 7' 9" and 6' 0" x 6' 0" **Space Requirements**: 113' 0" x 73' 3" *

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric;
 (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.