



Water Slide Model 9410

Specifications

Description: Double 30" I.D. flume slide with one (1) 90° curve & one (1) 360° turn.

Centerline Run: 31' 6" and 43' 1"

Entry Height: 10' 5"

Platform Size: 8' x 8'

Space Requirements: 33' 9" x 15' 2" *

Features

- 30" inside diameter polyethylene flumes.
- Flume: color impregnated UV stabilized.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: Spiral Stairs 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 20 gpm water flow (each flume) recommended; 20 to 40 gpm required.
- Splash down dimension: 41' 10" x 20'
- Minimum water depth: 3'
- USA Made

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.