



# Fiberglass Water Slide Model 1850

## Specifications

**Description:** Speed slide

**Centerline Run:** 65' 3"

**Entry Height:** 30' 8½"

**Platform Size:** *abstract size, approximately 6' 5" x 7' ½"*

**Space Requirements:** 14' 5" x 102' 0" \*

## Features

- 32" inside diameter closed flume fiberglass.
- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Self-enclosed recirculating system (no pool required)
- Fiberglass exit lane
- 150-200 gpm water flow required.
- Pool application also available
- Splash down dimension: 13' x 41' (for pool applications)
- Minimum water depth: 3' (for pool applications)
- USA Made

## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270 • Baker City OR 97814 • 800-252-8475 • [www.naturalstructures.com](http://www.naturalstructures.com) • Email: [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.