



# Water Slide Model 1628-RH 44

## Specifications

**Description:** Single 30" I.D. flume slide with one 270° turn.

**Centerline Run:** 40' 8"

**Entry Height:** 10' 5"

**Platform Size:** 4' x 4'

**Space Requirements:** 20' 11" x 18' 11" \*

## Features

- 30" inside diameter polyethylene water slide flume
- Water slide flume: color impregnated UV stabilized
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 8" rise, 8" tread, 24" wide; Aqua-Plast coated textured aluminum surface.
- Stainless steel base plates, hardware and anchor bolts
- Designed with flexibility to allow for sloping pool decks
- Deck top mounted
- 20 gpm water flow recommended; 20 to 40 gpm required.
- Splash down dimension 12' 6" x 20'
- Minimum water depth: 3'
- USA Made

## Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat, except stair treads and deck which are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available
- Stairs: (a) 7" rise, 11" tread, 36" or 48" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Stair Configurations: Many variations available
- Gates: Locking gate to water slide flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with the wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing around water slide
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.