



## Double Flume Hillside Slide Model: Ceta Canyon

### Specifications

**Description:** Double flume polyethylene body slides with fiberglass exit lanes  
**Centerline Run:** 156' 7" & 129' 2"

**Exit Lane Length:** 30' 0" and 40' 0"

**Entry Height:** 25' 0"

**Space Requirements:** 41' 2" x 135' 10"

### Features

- 30" inside diameter polyethylene flume.
- Flume: color impregnated UV stabilized.
- Stairs & Platform: *\*available - done by others*
- Stainless steel base plates, hardware and anchor bolts.
- Flume posts are required in accordance to the elevation.
- Fiberglass exit lanes.
- 50 gpm water flow (each flume) recommended; 30 to 60 gpm required
- Self-enclosed recirculating system (no pool required)
- USA Made.

### Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
 www.naturalstructures.com - info@naturalstructures.com

\*Space requirements may vary with options chosen.