



# Landscape Slide Model: DeRocker

## Specifications

**Description:** 30" I.D. Single polyethylene flume slide featuring 360° and 90° curves  
**Centerline Run:** 68' 11"

**Entry Height:** 14' 0"

**Platform Size:** \*Platform and stairs done by others.  
**Space Requirements:** 11' 10" x 31' 0" \*

## Features

- 30" Inside diameter polyethylene flume.
- Polyethylene Flume: Color impregnated UV stabilized.
- Stairs & Platform: Available.
- Water flow required: 20-40 gpm.
- Splash down dimension: 12' 6" x 20' 0"
- Minimum water depth: 5' 6"
- USA Made

## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814  
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231  
[www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.