

Hillside Slide Model: Mahoney

Specifications

Description: Single polyethylene flume

designed for hillside and landscape applications.

Centerline Run: 41' 2"

Features

- 30" inside diameter polyethylene flume.
- Polyethylene Flume: color impregnated UV stabilized.
- Stairs & Deck: available.
- Multiple stair locations & configurations.
- Stairs & Platform: determined by the slope.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 20 to 40 gpm required.
- Splash down dimension 12' 6" x 20' 0"
- Minimum water depth: 5' 0"
- USA Made

ftructures PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231 www.naturalstructures.com - info@naturalstructures.com

Slide Entrance Height: 10' 0"

Space Requirement: 17' 10" x 17' 3"

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- · Hot dipped galvanized available.
- Stairs: Aqua-Plast coated textured aluminum surface; closed risers (a) 7" rise, 11" tread, 36" wide
 (b) 48" width; (c) Inner handrails (if applicable)
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric;
 (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.