



## Pool Slide Model 0072

Note: Vertical slats now standard on all stair handrails.

### Specifications

**Description:** Single flume slide with one straight 24" O.D. flume.

**Centerline Run:** 12' 8"

**Entry Height:** 5' 6"

**Platform Size:** 4' x 4'

**Space Requirements:** 9' 0" x 15' 0" \*

### Features

- 24" outside diameter polyethylene flumes.
- Deck: Aqua-Plast coated textured aluminum surface.
- Stairs: 8" rise, 8" tread, 24" wide; Aqua-Plast coated textured aluminum surface.
- Multiple stair locations & configurations.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 10 gpm water flow recommended; 8 to 40 gpm required.
- Splash down dimension 12' x 20'
- Minimum water depth: 4' 0"
- USA Made

### Options

- Deluxe Series: Complete package is stainless steel polyester powder coated except the stair treads and deck which are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating with polyester powder coat topcoat, except stair treads and deck which are textured Aqua-Plast coated aluminum.
- Stairs: (a) 7" rise, 11" tread, 36" wide; textured aluminum; closed risers; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: Polyethylene plastic roof.
- Factory installation or on-site technical assistance.
- Water pumps & covers



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 [www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.