



Combination Water Slide Model 1873

Specifications

Description: Single open flume fiberglass body slide featuring (1) 180° and (2) 360° reverse curves and fiberglass speed slide.

Features

- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Water flow required: Body: 600-800 gpm; Speed: 150-200 gpm
- Splash down dimension: 23' 0" x 35' 0"
- Minimum water depth: 3' 0"
- USA Made

Centerline Run: Body 164' 10"; Speed 59' 0"

Entry Height: 22' 9"

Platform Size: 10' x 12'

Space Requirements: 36' 10" x 60' 2" *

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
(541) 523-0224 (800) 252-8475 Fax (541) 523-0231
www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.