



# Fiberglass Water Slide Model 1955

## Specifications

**Description:** Single open flume fiberglass slide with 2¼ spiral turns.

**Centerline Run:** 89' 7"

**Entry Height:** 18' 1"

**Platform Size:** 6' x 6'

**Space Requirements:** 25' 11" x 18' 6"

## Features

- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide spiral; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- 250-500 gpm water flow required.
- Splash down dimension: 13' 0" x 20' 0"
- Minimum water depth: 5' 6"
- USA Made



## Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable).
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 [www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)

\*Space requirements may vary with options chosen.