



Double Flume Fiberglass Water Slide Model 2040

Specifications

Description: Combination fiberglass flume water slide featuring: (1) 32" I.D. closed fiberglass flume (2) 32" I.D. closed & 36" I.D. open fiberglass flume.

Features

- 32" inside diameter fiberglass flume.
- 36" inside diameter fiberglass flume.
- Flume: ultra violet stabilized gelcoat.
- Platform: Aqua-Plast coated textured aluminum surface.
- Stairs: 7" rise, 11" tread, 36" wide; Aqua-Plast coated textured aluminum surface; closed risers.
- Stainless steel base plates, hardware and anchor bolts.
- Designed with flexibility to allow for sloping pool decks.
- Water flow required: Flume (1): 20-40 gpm; Flume (2): 200-500 gpm.
- Splash down dimension: 20' 0" x 22' 0"
- Minimum water depth: 3' 0"
- USA Made

Centerline Run: (1): 70' 4" (2): 96' 2"

Entry Height: (1): 16' 3" (2): 15' 9"

Platform Size: 4' x 14'

Space Requirements: 45' 8" x 25' 0" *

Options

- Deluxe Series: Stainless steel polyester powder coated except tower and flume posts which are mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- North Star Series: Mild steel with chemical resistant Aqua-Kote undercoating and polyester powder coat topcoat. Note: Platform and stair treads are textured Aqua-Plast coated aluminum.
- Hot dipped galvanized available.
- Stairs: (a) 48" width; (b) Inner handrails (if applicable); (c) Spiral stairs.
- Gates: Locking gate to flume entrance.
- Flag and banner holders.
- Tower Roof: (a) Steel; (b) Wood; (c) Fabric; (d) Tongue & groove decking with wood or steel roofs.
- Water pumps & covers
- Perimeter Fencing
- Factory installation or on-site technical assistance.



PO Box 270, Baker City, OR 97814
 (541) 523-0224 (800) 252-8475 Fax (541) 523-0231
 www.naturalstructures.com - info@naturalstructures.com

*Space requirements may vary with options chosen.