



\*Playground surfacing (by others) required.

**SAFETY NOTE:** All stainless steel slide bedway riding surfaces will get hot from direct sunlight exposure!  
It is highly recommended that the slide is installed on the job site with direct northern exposure placement and/or in a fully shaded area to minimize heat build up and transfer to users.

# Stainless Steel Embankment Slide Model SS-EMS0905-BM

## Specifications

**Description:** Stainless Steel Embankment Slide

**Entry Height:** 9' 0"

**Slide Inside Width:** 4' 8"

**Slide Run:** 17' 9"

**Stairs & Platform:** *By others*

**Space Requirements:** 5' 0" x 15' 0"

## Features

- 5' wide stainless steel open flume
- Widths available: 4' 0", 5' 0", & 6' 0"
- Heights available: 3' 0" - 10' 0"
- Bedway: 12 gauge stainless steel, 2B Mill finish
- Frame: Mild steel, powder coat finish
- Hardware: Zinc
- Entrance: Grab bar
- Buried or surface mount
- Made in the USA

## Options Shown

- Bury Mount

## Options

- Divided slide (center rail)
- Transfer station (sit down entrance)
- Installation Mount:
  - ▶ **BM** in model number indicates **Buried mount**
  - ▶ **SM** in model number indicates **Surface mount**



PO Box 270, Baker City, OR 97814 (541) 523-0224 (800) 252-8475 [www.naturalstructures.com](http://www.naturalstructures.com) - [info@naturalstructures.com](mailto:info@naturalstructures.com)